

# DVGW type examination certificate

## DVGW-Baumusterprüfzertifikat

**DV-8606BT0298**

Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of gas and water supply <i>Produkte der Gas- und Wasserversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	Kimplas Piping Systems LTD. B-20, MIDC, IND- Ambad, Nashik-422010
<b>Distributor</b> <i>Vertreiber</i>	Kimplas Limited Unit-2 Mushroom Farm Ind.Estate Hedingham Road, Weahterfield, GB- Braintree, Essex CM74EQ
<b>Product Category</b> <i>Produktart</i>	plastic fittings and compression fittings: PE-HD electro fusion fitting, diameter 75 up to 225 mm (8608)
<b>Product Description</b> <i>Produktbezeichnung</i>	electro fusion fittings made of PE-HD (PE 100) for gas and drinking water supply
<b>Model</b> <i>Modell</i>	TRUSTLENE; TRUSTLENE FLEXIFIT
<b>Test Reports</b> <i>Prüfberichte</i>	type testing: K 11 1140.6+K 11 0262.4 from 22.08.2011 (MPD) type testing: K 10 1456.6 from 09.08.2011 (MPD) KTW testing: K-203737-11-Ko from 30.05.2011 (WHY) hygienic testing: MO 088A/06 from 22.01.2007 (TZW)
<b>Test Basis</b> <i>Prüfgrundlagen</i>	DVGW GW 335-B2 (01.09.2004) UBA KTW (16.05.2007) DVGW W 270 (01.11.2007)

**Date of Expiry / File No.** 23.06.2013 / 10-0497-WNA  
*Ablaufdatum / Aktenzeichen*

26.09.2011 GI A-1/2

Date, issued by, Sheet, Head of Certification Body  
*Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle*

DVGW CERT GmbH is an accredited body by DAkkS according to EN  
45011:1998 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN 45011:1998 akkreditierte  
Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.

<b>Type</b> <i>Typ</i>	<b>Technical Data</b> <i>Technische Daten</i>	<b>Remarks</b> <i>Bemerkungen</i>
TRUSTLENE	nominal diameter: 75 mm	
TRUSTLENE	nominal diameter: 90 mm	
TRUSTLENE	nominal diameter: 110 mm	
TRUSTLENE	nominal diameter: 125 mm	
TRUSTLENE	nominal diameter: 140 mm	
TRUSTLENE	nominal diameter: 160 mm	
TRUSTLENE	nominal diameter: 180 mm	
TRUSTLENE	nominal diameter: 200 mm	
TRUSTLENE	nominal diameter: 225 mm	
TRUSTLENE FLEXIFIT	nominal diameter: 63 up to 75 mm	
TRUSTLENE FLEXIFIT	nominal diameter: 90 up to 140 mm	
TRUSTLENE FLEXIFIT	nominal diameter: 160 up to 225 mm	

<b>Type Variation</b> <i>Ausführungsvariante</i>	<b>Explanations</b> <i>Erläuterungen</i>
TRUSTLENE FLEXIFIT	flexible electro fusion tap

#### **Hints of Utilization / Remarks**

#### **Verwendungshinweise / Bemerkungen**

material: Borstar HE 3490-IM (Borealis AG)