



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DV-8608BT0671

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas and water supply <i>Produkte der Gas- und Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Kimplas Piping Systems LTD. B-20, MIDC, IND- Ambad, Nashik-422010
Distributor <i>Vertreiber</i>	Kimplas Ltd. 24, First Avenue, Blue Bridge Ind., GB- Halstead, Essex, CO9 2EX
Product Category <i>Produktart</i>	plastic fittings and compression fittings: PE-HD electro fusion fitting, diameter 75 up to 225 mm (8608)
Product Description <i>Produktbezeichnung</i>	electro fusion fittings made of PE-HD (PE 100) for gas and drinking water supply
Model <i>Modell</i>	TRUSTLENE FLEXIFIT
Test Reports <i>Prüfberichte</i>	laboratory control test: K 17 0210.4 from 05.05.2017 (MPD) type testing: K 15 1417.5 from 27.04.2016 (MPD) type testing: K071277.1 from 23.06.2008 (MPD) KTW testing: K-274363-16-Ko/st from 18.08.2016 (WHY) hygienic testing: MO 111/17 from 16.10.2017 (TZW) KTW testing: K-265759-16-Ko from 05.01.2016 (WHY) hygienic testing: MO 008/15 from 17.02.2015 (TZW)
Test Basis <i>Prüfgrundlagen</i>	DVGW GW 335-B2 (01.09.2004) DVGW GW 335-B2/B1 (01.02.2013) UBA KTW (07.03.2016) DVGW W 270 (01.11.2007)
Date of Expiry / File No. <i>Ablaufdatum / Aktenzeichen</i>	23.06.2023 / 18-0262-WNV

7028-04-A-DE

01.06.2018 GI A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
TRUSTLENE FLEXIFIT	nominal diameter: 63 up to 75 mm	
TRUSTLENE FLEXIFIT	nominal diameter: 90 up to 140 mm	
TRUSTLENE FLEXIFIT	nominal diameter: 160 up to 225 mm	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
TRUSTLENE FLEXIFIT	flexible electro fusion tapping tees

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

material: Borstar HE 3490-IM (Borealis AG) and CRP 100 black (Basell)

The requirements of DIN EN 1555-3 (2011-08) and DIN EN 12201-3 (2011-11) are fulfilled.

DWG