


Electrofusion Equal Tee for Gas - SDR11 (ISO S5)



d	PRODUCT CODE	SP	g	D	d	d ₁	L	H	F-T	C-T
	PE80 Yellow 4,7mm Pin Terminal									
20	201050101010101	120	69	32	20	20	90	83	22	4
25	201050201010101	90	64	35	25	25	90	86	28	4
32	201050301010101	60	94	45	32	32	101	96	42	4
63	201050601010101	14	379	82	63	63	151	160	70	7
90	201050801010101	4	922	113	90	90	220	218	140	15
110	201050901010102	3	1384	137	110	110	252	253	160	15
125	201051001010101	2	2024	155	125	125	256	267	200	15

Note : SP = Standard Pack Quantity, g = Weight in Grams, F-T = Fusion Time in Seconds, C-T = Cooling Time in Minutes

Kimplas Electrofusion Tees, manufactured in PE80 (Yellow) grade are Standard SDR 11 rated. For exact recommendations on compatibility for welding with SDR 9 through SDR 21 Pipes, refer Kimplas Technical Specifications Manual.

Kimplas Electrofusion Equal Tees are suitable for permanently connecting PE 80 pipes, both in straight as well as coil form.

Standards:

- PE Pipe Compatibility : IS:14885, ISO:4437, EN:1555-1, GIS PL 2 /2
- Complies with GIS PL 2 /4

Common Applications:

- ✓ Make Branch Connections on mains and distribution pipes in a distribution network
- ✓ Taking Branch Connections in narrow trenches, in areas difficult to access
- ✓ House Service Connections
- ✓ Pipe Connections with spigot end fittings, pipe stub ends etc

Installation :

Joint preparation must be done as specified in the installation instructions. Pipe outside surface must be scraped to remove oxidized layer. Before fusing, pipe ends and inside of the fittings must be cleaned to remove dirt and contamination. Complete Installation Manual may be downloaded.

Advantages:

- Standard Operating Voltage - 40 V
- Same fusion time for various SDR rated pipes
- Higher penetration of pipe in the fittings enables proper alignment
- Optimal fusion and cold zone for a strong and sturdy joint
- Auto Temperature compensation for ambient conditions -5°C to + 40°C
- Clearance-Fit for ease of installation
- Pop-Up fusion indicators to indicate fusion process performance
- Permanent Batch Indicator, Fusion Time, Cooling Time, Raw Material Grade and SDR marking
- Each fitting individually packed in PE bag to protect against contamination and oxidation
- Each fitting with water-proof bar code to automatically feed fusion data to the Control-box for fusion process