


COMPRESSION - FEMALE THREADED BALL VALVE



d	DN	ITEM Code	g	SP	L	D	H	A	X" BSP	D1
20	15	207400301010101	116	100	96	49	52	60	1/2"	43
25	20	207400201010101	184	65	115	60	58	65	3/4"	54
32	25	207400101010101	274	42	128	68	66	75	1"	65

Note : SP - Standard Packing Quality, g - Individual fitting weight in gms

Kimplas UPVC Ball Valves are designed to use with threaded PVC and metal pipes Kimplas PVC Ball Valves are ideally suited for connecting Drip and Sprinkler Irrigation piping networks. The Valves are recommended for Cold Water Services within temperature range of 0°C to 40° C.

For exact recommendations on use and applications, refer Kimplas Technical Specifications Manual.

Standards:

- Pipe compatibility: IS:4984, IS:12786, ISO:4427, EN:12201-1, DIN:8074
- Dimensions, Features & Functional Tests: ISO:3501, ISO:3503, ISO:3459
- Threading: IS:554, ISO:7/1, DIN:2999
- Comply with ISO:1452 - Part 4 & IS:14236

Common Applications:

- ✓ PE Pipe to Threaded pipe or fitting connection during laying
- ✓ For connecting Sprinkler Irrigation mains and sub-mains
- ✓ For connecting fertigation equipment like Venturi, Fertilizer Tank, Dozing pump etc.

Installation :

Joint preparation must be done as specified in the installation instructions. Complete Installation Manual may be downloaded.

Female Threaded Valve:

Pipe ends must be cut square and burr-free before using with the valve. Chamfer may be provided on the PE pipe end to facilitate ease of pipe insertion. To install the valve, there is no need to open the nut and other components of the fitting. To install the fitting, just loosen the nut by three to four turns, insert the pipe into the fitting until the pipe crosses the rubber seal and stops at the pipe stop. Then tighten the nut by hands only. The nut should be closed tightly, however there is no need for the nut to actually meet the body. On the threaded side, threaded pipe shall be screwed on by using sealant tape (Teflon or plumber's tape).

Advantages :

- All body parts exposed to Sun are duly UV stabilized
- Plastic & rubber materials conform to the Standard requirements for use with Irrigation water
- The Body & nut made up of PVC with its sturdy design holds the pipe-fitting assembly intact with continuous working pressures upto 16 Bars
- The grip ring made up of POM (Poly-acetal) prevents the pipe being pulled out from the fitting
- Full bore cross section for higher flow
- The PP (Packing Pressure) Bush exerts thrust on the rubber O'-Ring / Gasket, compresses on pipe and fitting body to ensure leak-tightness.
- Rubber O'-Ring / Gasket prevent leakage under internal pressure as well as under external pressure as in case of vacuum and/or suction.
- Resistant to a wide range of chemicals
- Threaded connections conform to IS: 554 (BSPT)
- Higher penetration of pipe in fittings enables proper alignment
- Clearance-Fit for ease of installation and repairs
- Tolerance fit to take care of ovality of coiled pipes
- Permanent Batch Indicator, Size, PN rating and Raw Material Grade marking for ease of traceability
- Compact but sturdy design for ease of installation and trouble free service